

2" Compact Submersible Water Pump

- Self-priming, compact, lightweight design with carrying handle
- High impact strainer housing
- Up to 275 gpm (1,041 lpm)
- Can draw water down to depth of 1-3/4" (45 mm)
- Can run dry without damage
- Locking coupler for discharge hose included



H4665A

SPECIFICATIONS

System	Open and Closed Center
Capacity	Up to 275 gpm (1,041 lpm) [at 7 gpm (27 lpm) and a 10' (3 m) head height]
Intake Port	1-15/16" (49 mm)
Discharge Port	2" (44 mm) NPT Female
Strainer	2-5/8 x 5-58" (67 x 143 mm) – 3/8" (9.5 mm) openings
Weight	9 lb (4.0 kg)
Height	12.5" (318 mm) over handle
Width	7.5" (190 mm) diameter
Flow Range	5 – 8 gpm (19 – 30 lpm)
Operating Pressure	0 – 2,000 psi (0 – 138 bar)
Pressure Port Thread	9/16 – 18 SAE O Ring
Return Port Thread	3/4 – 16 SAE O Ring



F024772



156340

CAT. NO.	UPC NO.	DESCRIPTION
H4665A	783310421917	Compact Submersible Pump
A F024772	783310421047	2" Cam Lock Coupling for Discharge Hose
A 156340	783310412205	2" Diameter x 25' Discharge Hose Assembly
A 54923	783310549239	HTMA Male Coupler
A 54924	783310549246	HTMA Female Coupler

2-1/2" Submersible Water Pump

- High impact strainer housing with carrying handle
- Self priming
- Up to 400 gpm (1,514 lpm)
- Pump is able to run dry for longer working life
- Can draw water down to depth of 2" (51 mm)
- Locking coupler for discharge hose included



SPECIFICATIONS

System	Open and Closed Center
Capacity	Up to 400 gpm (1,514 lpm) [at 7 gpm (27 lpm) and a 15' (4.5 m) head height]
Intake Port	1-1/2" (38 mm)
Discharge Port	2-1/2" (64 mm) NPT Female
Strainer	7" x 2.5" (178 x 64 mm)
Weight	23.5 lb (10.6 kg)
Height	16" (406 mm) over handle
Width	12" (305 mm) diameter
Flow Range	4 – 8 gpm (15 – 30 lpm)
Operating Pressure	0 – 2,000 psi (0 – 138 bar)
Pressure Port Thread	1/2" Male NPTF
Return Port Thread	1/2" Male NPTF



F024775



156339

CAT. NO.	UPC NO.	DESCRIPTION
H4660B	783310421900	Submersible Pump
A F024775	783310421054	2.5" Cam Lock Coupling for Discharge Hose
A 156339	783310412199	2.5" Diameter x 25' Discharge Hose Assembly
A F020196K	783310417781	HTMA Female Coupler – 1/2" NPTF internal thread
A F020197K	783310417798	HTMA Male Coupler – 1/2" NPTF internal thread

3" Submersible Trash Pump

- Compact, under 12" (300 mm) diameter to easily fit into small areas
- Self-priming submersible pump can be placed and operated quickly
- Passes up to 3" (76 mm) solids minimizing pump blockage from debris
- Pump is able to run dry for longer working life
- Carry handle with lifting eye makes it easy to transport, move, lift, and lower
- Locking coupler for discharge hose included
- Can draw water down to depth of 2-3/4" (70 mm)



H4635

SPECIFICATIONS

System	Open and Closed Center
Capacity	Up to 500 gpm (1893 lpm) [at 8 gpm (30 lpm) and a 15' (4.5 m) head height]
Intake Port	3.125" (79.4 mm)
Discharge Port	3" (76.2 mm) NPT Female
Trash Diameter	3" (76 mm)
Weight	28 lb (11.7 kg)
Height	14.18" (360 mm) over handle
Width	11.87" (301 mm) diameter
Flow Range	7 – 10 gpm (26.5 – 37.9 lpm)
Operating Pressure	0 – 2,000 psi (0 – 138 bar)
Pressure Port Thread	1/2" Male NPTF
Return Port Thread	1/2" Male NPTF



49499

CAT. NO.	UPC NO.	DESCRIPTION
H4635	783310493341	Hydraulic 3" Trash Pump
A 49499	783310494997	3" Diameter x 25' Discharge Hose Assembly
A F020196K	783310417781	HTMA Female Coupler – 1/2" NPTF internal thread
A F020197K	783310417798	HTMA Male Coupler – 1/2" NPTF internal thread