



H4802 5







H4802

Pole Tampers

- Makes quick work of setting poles, asphalt patch, and general construction backfill compacting
- Only three moving parts for low maintenance
- Kidney-shaped foot included
- Hose End Valve – Reversible on/off valve for Open and Closed-Center hydraulic systems
- Valve on Tube – Rotate trigger spool for Open and Closed Center hydraulic systems

SPECIFICATIONS

Valve Location	H4802 6 – Hose End H4802 5 and H4802 3 – On Tube
Length	H4802 – 60" (1.5 m); H4802-6 – 60" (1.5 m); H4802-1 – 85" (2.2 m); H4802-5 – 60" (1.5 m); H4802-3 – 72" (1.8 m)
Weight	H4802 – 23 lb (10.4 kg); H4802-6 – 23 lb (10.4 kg); H4802-1 – 28 lb (12.7 kg); H4802-5 – 22 lb (9.8 kg); H4802-3 – 23 lb (10.4 kg)
System	Open and Closed Center
Width	4" (102 mm)
Flow Range	4 – 6 gpm (15 – 23 lpm)
Operating Pressure	1,000 – 2,000 psi (69 – 138 bar)
Pressure Port Thread	9/16 – 18 SAE O Ring
Return Port Thread	3/4 – 16 SAE O Ring
Standard Foot Size	2.5 x 8" (63 x 203 mm) kidney-shaped
Blows Frequency	1,160/min. at 5 gpm (19 lpm)

CAT. NO.	UPC NO.	DESCRIPTION
H4802	783310421986	60" Pole Tamper, Hose End Valve
H4802-6	783310422020	60" Pole Tamper, Hose End Valve (unit does not include on/off valve)
H4802-1	783310421993	85" Pole Tamper, Hose End Valve
H4802-5	783310422013	60" Pole Tamper, Valve on Tube
H4802-3	783310422006	72" Pole Tamper, Valve on Tube
 111964K	783310403012	Kidney-Shaped Foot
 54923	783310549239	HTMA Male Coupler
 54924	783310549246	HTMA Female Coupler
 56295	783310562955	56" Abrasion Resistant Hose Set w/nylon sleeve and tool end strain reliefs
 56296	783310562962	56" Hose Set for Remote Valve Tampers w/tool end strain reliefs
 HRV48	783310072294	Remote Valve