

Technical data Mini Lifting Bags

Mini Lifting Bags 116 psi (with aramid reinforcement)									
Typ	Unit	V 1	V 3	V 5	V 6	V 10	V 12	V 18	V 20
Item no.		1314 0093 00	1314 0095 00	1314 0182 00	1314 0096 00	1314 0022 00	1314 0024 00	1314 0025 00	1314 0118 00
Lifting capacity, max.	US tons	1,1	3,6	5,7	6,3	10,6	13,2	19,5	21,4
Lifting height, max.	inch	3,0	4,7	5,7	6,5	8,0	7,9	10,6	11,0
Size	inch	5,5 x 5,1	10 x 7,9	11 x 11	11,6 x 11,6	14,6 x 14,6	12,6 x 20,5	18,5 x 20,5	18,9 x 22,8
Insertion height	inch	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0
Air Requirement	cu.ft.	0,1	0,6	1,0	1,4	2,9	3,4	6,9	7,9
Operating overpressure, max.	psi	116	116	116	116	116	116	116	116
Test pressure	psi	203	203	203	203	203	203	203	203
Weight approx.	lbs	1,1	2,2	3,1	4,2	7,3	8,6	12,6	13,7
Typ	Unit	V 24	V 24 L	V 31	V 35 L	V 40	V 48	V 54	V 68
Item no.		1314 0026 00	1314 0027 00	1314 0028 00	1314 0183 00	1314 0029 00	1314 0283 00	1314 0030 00	1314 0031 00
Lifting capacity, max.	US tons	26,5	26,5	34,6	39,5	43,7	54,3	60,0	74,6
Lifting height, max.	inch	12,0	7,9	14,6	12,2	15,8	17,9	18,8	20,5
Size	inch	20,5 x 24,4	12,2 x 40,2	25,6 x 27,2	16,9 x 45,3	30,7 x 27,2	32,3 x 32,3	33,9 x 33,9	37,4 x 37,4
Insertion height	inch	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0
Air Requirement	cu.ft.	10,5	7,5	18,3	12,3	23,8	31,8	39,5	51,5
Operating overpressure, max.	psi	116	116	116	116	116	116	116	116
Test pressure	psi	203	203	203	203	203	203	203	203
Weight approx.	lbs	15,9	15,0	22,3	22,0	26,9	31,7	38,1	45,6

All rights reserved for technical changes within the scope of product improvement.